





Compliant SDS for GHS: HazCom 2012 / United States; WHMIS 2015 / Canada

#### SAFETY DATA SHEET

Synthetic Powershift Transmission Fluid, SAE 30, Synthetic Powershift Transmission Fluid, SAE 50

**Section 1. Identification** 

Date : 11/30/2016

Version: 7

**GHS** product identifier

 Synthetic Powershift Transmission Fluid, SAE 30, Synthetic Powershift Transmission Fluid, SAE 50

Code

: CTJ, CTL : Liquid.

Product type

Identified uses

: Transmission Fluid.

Manufacturer

: AMSOIL INC. One AMSOIL Center

Superior, WI 54880 Tel: +1 715-392-7101

Initial Supplier (Canada)

: AMSOIL INC.

Bordner, Ladner, Gervais Scotia Plaza, 40 King St W Toronto, ON, Canada M5H 3Y4

Tel: +1 416-367-6547

Emergency telephone number (with hours of

operation)

: CHEMTREC: Within USA and Canada: 1-800-424-9300;

Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

(24/7)

### Section 2. Hazards identification

**OSHA/HCS status** 

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

: EYE IRRITATION - Category 2A
TOXIC TO REPRODUCTION (Fertility) - Category 2
TOXIC TO REPRODUCTION (Unborn child) - Category 2

AQUATIC HAZARD (ACUTE) - Category 3 AQUATIC HAZARD (LONG-TERM) - Category 3

**GHS label elements** 

Hazard pictograms





Signal word

: Warning

**Hazard statements** 

: Causes serious eye irritation.

Suspected of damaging fertility or the unborn child. Harmful to aquatic life with long lasting effects.

### FREE CATALOG

SAVE UP TO 25%

Synthetic Powershift Transmission Fluid, SAE 30, Synthetic Powershift Transmission Fluid, SAE 50

CTJ, CTL

#### Precautionary statements

Prevention

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Avoid release to the environment. Wash hands thoroughly after handling.

Response

: IF exposed or concerned: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

**Storage** 

: Store locked up.

**Disposal** 

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

#### **Hazards not otherwise classified (HNOC)**

Physical hazards not otherwise classified

(PHNOC)

: None known.

Health hazards not otherwise classified

(HHNOC)

: None known.

### Section 3. Composition/information on ingredients

Substance/mixture

Other means of identification

: Not available.

: Mixture

#### **CAS** number/other identifiers

CAS number : Not applicable.

Product code : CTJ, CTL

Ingredient name	%	CAS number
Zinc Alkyldithiophosphate	1 - 5	68649-42-3
Hydrogenated Base Oil (64742-55-8)	0.1 - 1	64742-55-8
p-Dodecylphenol	0.1 - 1	104-43-8
Cadmium (Non-pyrophoric)	0 - 0.1	7440-43-9

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### **Description of necessary first aid measures**

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Get medical attention.

SAVE UP TO 25%

Synthetic Powershift Transmission Fluid, SAE 30, Synthetic Powershift Transmission Fluid, SAE 50

CTJ, CTL

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Skin contact** 

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 20 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.
 Skin contact : No known significant effects or critical hazards.
 Ingestion : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

**Eye contact**: Adverse symptoms may include the following:

pain or irritation watering redness

**Inhalation** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion**: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments**: No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may

be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Synthetic Powershift Transmission Fluid, SAE 30, Synthetic Powershift Transmission Fluid, SAE 50

CTJ, CTL

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

#### **Extinguishing media**

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

 Decomposition products may include the following materials: carbon dioxide carbon monoxide

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and materials for containment and cleaning up

# FREE CATALOG

SAVE UP TO 25%

Synthetic Powershift Transmission Fluid, SAE 30, Synthetic Powershift Transmission Fluid, SAE 50

CTJ, CTL

Spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

### Section 7. Handling and storage

#### Precautions for safe handling

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Avoid contact with used product. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

Occupational exposure limits

Under conditions which may generate mists, the following additional exposure limits are recommended: ACGIH TLV TWA: 5 mg/m3; STEL: 10 mg/m3.

**United States** 

# SAVE UP TO 25%

Synthetic Powershift Transmission Fluid, SAE 30, Synthetic Powershift Transmission Fluid, SAE 50

CTJ, CTL

Ingredient name	Exposure limits
Cadmium (Non-pyrophoric)	OSHA PEL Z2 (United States, 2/2013).  TWA: 0.2 mg/m³ 8 hours. Form: Dust CEIL: 0.6 mg/m³ Form: Dust TWA: 0.1 mg/m³ 8 hours. Form: Fume CEIL: 0.3 mg/m³ Form: Fume ACGIH TLV (United States, 3/2015).  TWA: 0.01 mg/m³, (as Cd) 8 hours. Form: Inhalable fraction TWA: 0.002 mg/m³, (as Cd) 8 hours. Form: Respirable fraction OSHA PEL (United States, 2/2013).  TWA: 5 μg/m³, (as Cd) 8 hours.

#### Canada

#### Occupational exposure limits

None.

# Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

# **Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

#### **Individual protection measures**

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

#### **Skin protection**

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

#### **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

#### **Respiratory protection**

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Synthetic Powershift Transmission Fluid, SAE 30, Synthetic Powershift Transmission Fluid, SAE 50

CTJ, CTL

### Section 9. Physical and chemical properties

**Appearance** 

Physical state : Liquid.
Color : Red.

Odor : Mild hydrocarbon.
Odor threshold : Not available.
pH : Not available.

**Melting point** : -40 to -39°C (-40 to -38.2°F)

Boiling point : Not available.

Flash point : Open cup: 232 to 238°C (449.6 to 460.4°F) [Cleveland.]

Evaporation rate : Not available.

Flammability (solid, gas) : Not available.

Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure : Not available.
Vapor density : Not available.
Relative density : 0.8745 to 0.8855
Solubility : Not available.
Partition coefficient: n- : Not available.

octanol/water

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Kinematic: 0.11 to 0.189 cm<sup>2</sup>/s (11 to 18.9 cSt) (100°C)

Kinematic: 0.765 to 1.74 cm<sup>2</sup>/s (76.5 to 174 cSt) (40°C)

Volatility : Not available.

## Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability**: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

**Incompatible materials** : Reactive or incompatible with the following materials: oxidizing materials.

SAVE UP TO 25%

Synthetic Powershift Transmission Fluid, SAE 30, Synthetic Powershift Transmission Fluid, SAE 50

CTJ, CTL

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### **Section 11. Toxicological information**

#### Information on toxicological effects

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Cadmium (Non-pyrophoric)	LD50 Oral	Rat	2330 mg/kg	-

#### **Irritation/Corrosion**

There is no data available.

#### **Sensitization**

There is no data available.

#### **Carcinogenicity**

#### **Classification**

Product/ingredient name	OSHA	IARC	NTP
Cadmium (Non-pyrophoric)	+	1	Known to be a human carcinogen.

#### Specific target organ toxicity (single exposure)

There is no data available.

#### Specific target organ toxicity (repeated exposure)

Name	Category	Target organs
Cadmium (Non-pyrophoric)	Category 1	Not determined

#### **Aspiration hazard**

There is no data available.

Information on the likely routes of exposure

: Dermal contact. Eye contact. Inhalation. Ingestion.

#### Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Inhalation
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

pain or irritation watering redness

**Inhalation** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

SAVE UP TO 25%

Synthetic Powershift Transmission Fluid, SAE 30, Synthetic Powershift Transmission Fluid, SAE 50

CTJ, CTL

**Skin contact**: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion**: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

#### Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

**Potential immediate** 

effects

: No known significant effects or critical hazards.

Potential delayed effects

**Potential delayed effects** 

: No known significant effects or critical hazards.

**Long term exposure** 

**Potential immediate** 

effects

: No known significant effects or critical hazards.

: No known significant effects or critical hazards.

Potential chronic health effects

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : Suspected of damaging the unborn child.

**Developmental effects**: No known significant effects or critical hazards.

Fertility effects : Suspected of damaging fertility.

#### Numerical measures of toxicity

#### **Acute toxicity estimates**

Route	ATE value
Inhalation (dusts and mists)	150 mg/L

# **Section 12. Ecological information**

#### **Toxicity**

Product/ingredient name	Result	Species	<b>Exposure</b>
p-Dodecylphenol	Acute LC50 140 μg/l	Fish - Salmo salar	96 hours
Cadmium (Non-pyrophoric)	Acute EC50 97 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata - Exponential growth phase	72 hours
	Acute EC50 0.095 mg/L Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 200 µg/l Fresh water	Aquatic plants - Lemna minor	4 days
	Acute EC50 13.5 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 0.072 µg/l Marine water	Crustaceans - Amphipoda - Adult	48 hours
	Acute LC50 1 µg/l Fresh water	Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
	Chronic NOEC 2 μg/l Fresh water	Algae - Parachlorella kessleri - Exponential growth phase	72 hours

### FREE CATALOG

# SAVE UP TO 25%

Synthetic Powershift Transmission Fluid, SAE 30, Synthetic Powershift Transmission Fluid, SAE 50

CTJ, CTL

Chronic NOEC 0.02 μg/l Fresh water Fish - Cyprinus carpio 4 weeks

#### Persistence and degradability

There is no data available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
p-Dodecylphenol	7.91	-	high

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

: There is no data available.

Other adverse effects

: No known significant effects or critical hazards.

## **Section 13. Disposal considerations**

#### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **Section 14. Transport information**

	DOT	TDG	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-

# SAVE UP TO 25%

Synthetic Powershift Transmission Fluid, SAE 30, Synthetic Powershift Transmission Fluid, SAE 50

CTJ, CTL

Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

**AERG**: Not applicable.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the

event of an accident or spillage.

Transport in bulk according to Annex II of MARPOL and

the IBC Code

: Not available.

## **Section 15. Regulatory information**

**U.S. Federal regulations** : United States inventory (TSCA 8b): All components are listed or exempted.

Clean Water Act (CWA) 307: Zinc Alkyldithiophosphate: Arsenic: Cadmium (Non-

pyrophoric); Lead; Ethylbenzene; Naphthalene; Benzene

Clean Water Act (CWA) 311: Ethylbenzene; Xylene; Naphthalene; Benzene

**Clean Air Act Section 112** 

(b) Hazardous Air **Pollutants (HAPs)**  : Listed

Clean Air Act Section 602

**Class I Substances** 

: Not listed

Clean Air Act Section 602

**Class II Substances** 

: Not listed

**DEA List I Chemicals** 

(Precursor Chemicals)

: Not listed

**DEA List II Chemicals** (Essential Chemicals) : Not listed

**SARA 302/304** 

**Composition/information on ingredients** 

No products were found.

**SARA 304 RQ** : Not applicable.

**SARA 311/312** 

Classification : Immediate (acute) health hazard

Delayed (chronic) health hazard

**Composition/information on ingredients** 

Synthetic Powershift Transmission Fluid, SAE 30, Synthetic Powershift Transmission Fluid, SAE 50

CTJ, CTL

Name	hazard	Sudden release of pressure		Immediate (acute) health hazard	Delayed (chronic) health hazard
p-Dodecylphenol	No. No. No. No.	No. No. No.	No. No. No. No.	Yes. Yes. Yes. Yes.	No. No. Yes. Yes.

#### **SARA 313**

	Product name	CAS number	%
Form R - Reporting requirements	1	68649-42-3 7439-92-1	1 - 5 0 - 0.1
Supplier notification	Zinc Alkyldithiophosphate	68649-42-3	1 - 5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

#### **State regulations**

Massachusetts : None of the components are listed.

New York : None of the components are listed.

New Jersey : The following components are listed: Zinc Alkyldithiophosphate

Pennsylvania : None of the components are listed.

#### California Prop. 65

**WARNING:** This product contains less than 0.1% of a chemical known to the State of California to cause cancer. **WARNING:** This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Ethylbenzene	Yes.	No.	41 μg/day (ingestion) 54 μg/day (inhalation)	No.
Benzene	Yes.	Yes.	6.4 μg/day (ingestion) 13 μg/day (inhalation)	24 μg/day (ingestion) 49 μg/day (inhalation)
Naphthalene	Yes.	No.	Yes.	No.
Cadmium (Non-pyrophoric)	Yes.	Yes.	0.05 µg/day (inhalation)	4.1 µg/day (ingestion)
2-Propenoic acid, ethyl ester	Yes.	Yes.	No.	No.
Ethyl acrylate	Yes.	No.	No.	No.
Arsenic	Yes.	No.	0.06 μg/day (inhalation)	No.
Lead	Yes.	Yes.	15 μg/day (ingestion)	Yes.

#### **Canada**

**Canadian lists** 

Canadian NPRI : The following components are listed: Zinc Alkyldithiophosphate

CEPA Toxic substances : None of the components are listed.Canada inventory : All components are listed or exempted.

FREE CATALOG

**SAVE UP TO 25%** 

Synthetic Powershift Transmission Fluid, SAE 30, Synthetic Powershift Transmission Fluid, SAE 50

CTJ, CTL

### **Section 16. Other information**

#### **History**

Date of issue mm/dd/yyyy : 11/30/2016 Date of previous issue : 01/01/2015

Version : 7

Prepared by : AMSOIL INC.

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.